

Features

- 4-line alphanumeric display, (20 characters per line)
- Up to 30 personal message slots
- Up to 15 maildrops
- Time and date display
- Time and date stamping
- Unread message reminder alert
- Protect up to 15 personal, 16 notebook messages
- 5 history records in maildrop
- Maildrop alert - individual slot control
- Battery level indicator
- Out-of-range indicator
- Continuous message indicator
- EL back light
- Memory retention
- 1 daily alarm
- Vibrate/ 8 pleasing/ vibrate then audible/ no alert
- 3-speed page scrolling
- Zoom in from 4-line to 2-line display
- Adjustable LCD contrast (0-7 level)
- Low cell reminder
- Priority call
- 4 selectable alert durations; 8sec/16sec/40sec/continuous (PPS option)
- 3 selectable alert modes; Standard/Audio/ No Alert (PPS option)
- Tone message (PPS option)

Synthesized FLEX™ 4-line Alphanumeric Pager



Specifications

Model no.	BRAVO 800	
Frequency:	VHF (135 - 175MHz), 280 MHz (278-284MHz), 900MHz (929-932MHz)	
Code Format:	FLEX, 1600/3200/6400 bps	
Channel Spacing:	25 kHz	
Frequency Deviation:	+/- 4.8 kHz	
Paging Sensitivity:	-104 dBm (c.f. 22.5dB)	
	VHF	900MHz
EIA Selectivity:	50 dB	40 dB
EIA Spurious and Image:	50 dB	40 dB
IM Rejection:	50 dB	40 dB
Operating Temperature:	-10°C to 50°C	5°C to 40°C
Alert Tone Loudness:	75 dB @ 12 inches	
Battery Type:	1 x Alkaline AA	
Weight (with battery):	65 grams	
Dimensions:	80 x 54 x 19 mm	



RAD DEV FOR HAZ LOC INT SAFE
CI.I,Div1,Gr.CD, CI.I,Div2,Gr.ABCD, Exia, T4